

Item description/product images

**Description****Material:**

EN-GJL-250

Version:

Bright, ground.

Note:

These roller-mounted precision slides are used to build machines and mechanical systems, in metrology devices, optical instruments and precision mechanical engineering.

The stated permissible load values (F) are designed for a service life of 1 million lifting operations.

The torque values apply only to centred slides.

Cross slides are also available on request.

An additional centring hole is located at holes D2 and D3 on the top of the slide. Other connecting elements can be precisely mounted on the slide in combination with our centring rings 20240.

F = permissible loading for dynamic and static loads.


TI E/E1 = number of fastening holes E/E1/M in the internal part.

TA E/E1 = number of fastening holes E/E1/M in the external part.

TI E2 = number of fastening holes E2/D1 in the internal part.

TA E2 = number of fastening holes E2/D1 in the external part.

Drawings



Overview of items

Order No.	A	A1	A2	B	B1	C	D1	D2	D3	D4	E	E1	E2	E3	T1 E/E1	TA E/E1	T1 E2	TA E2
21064-040050	20	13	13	40	39,5	10	5	M3	3,3	6,5	30	15	20	20	4	4	6	6
21064-0400501	20	13	13	40	39,5	17,5	5	M3	3,3	6,5	30	15	20	20	4	4	6	6
21064-040065	20	13	13	40	39,5	25	5	M3	3,3	6,5	30	15	20	20	6	6	6	6
21064-040080	20	13	13	40	39,5	32,5	5	M3	3,3	6,5	30	15	20	20	8	8	6	6
21064-050055	25	17	16,3	50	49,5	10	7	M4	4,3	8	-	-	14	28	-	-	6	6
21064-050080	25	17	16,3	50	49,5	30	7	M4	4,3	8	-	-	28	28	-	-	6	6
21064-050105	25	17	16,3	50	49,5	40	7	M4	4,3	8	-	-	28	28	-	-	8	8

Overview of items

Order No.	A	A1	A2	B	B1	C	D1	D2	D3	D4	E	E1	E2	E3	T1 E/E1	TA E/E1	T1 E2	TA E2
21064-050155	25	17	16,3	50	49,5	60	7	M4	4,3	8	-	-	28	28	-	-	12	12
21064-060055	25	17	16,3	60	59,5	10	7	M4	4,3	8	-	-	17	34	-	-	6	6
21064-060080	25	17	16,3	60	59,5	30	7	M4	4,3	8	-	-	34	34	-	-	6	6
21064-060105	25	17	16,3	60	59,5	40	7	M4	4,3	8	-	-	34	34	-	-	6	6
21064-060155	25	17	16,3	60	59,5	60	7	M4	4,3	8	-	-	34	34	-	-	10	10
21064-075080	32	20	23	75	74,5	15	10	M5	5,3	10	62	62	25	50	4	4	6	4
21064-075105	32	20	23	75	74,5	20	10	M5	5,3	10	62	62	25	50	4	4	6	6
21064-075130	32	20	23	75	74,5	25	10	M5	5,3	10	62	62	25	50	4	4	8	8
21064-100110	40	27,5	28	100	99,5	15	10	M5	5,3	10	86	86	25	50	4	4	6	6
21064-100160	40	27,5	28	100	99,5	52,5	10	M5	5,3	10	86	86	50	50	4	4	12	12
21064-100210	40	27,5	28	100	99,5	80	10	M5	5,3	10	86	86	50	50	6	6	8	8
21064-100260	40	27,5	28	100	99,5	105	10	M5	5,3	10	86	86	50	50	4	6	10	10

Order No.	L	L2	L3	P	P1	M	M1	M2	T1	T2	F N	Mx Nm	My Nm	Mz Nm
21064-040050	50	34	3,8	1,1	3,4	M3	M3	M3	0,02	0,02	210	1	4	3
21064-0400501	50	34	3,8	1,1	3,4	M3	M3	M3	0,02	0,02	140	1	3	2
21064-040065	65	34	3,8	1,1	3,4	M3	M3	M3	0,02	0,02	180	1	4	3
21064-040080	80	34	3,8	1,1	3,4	M3	M3	M3	0,02	0,02	220	3	5	5
21064-050055	55	40	5,5	1,6	3,2	-	M3	M4	0,02	0,02	480	4	7	6
21064-050080	80	40	5,5	1,6	3,2	-	M3	M4	0,02	0,02	410	3	9	7
21064-050105	105	40	5,5	1,6	3,2	-	M3	M4	0,02	0,02	520	10	11	15
21064-050155	155	40	5,5	1,6	3,2	-	M3	M4	0,02	0,02	680	23	19	33
21064-060055	55	50	5,5	1,6	3,2	-	M3	M4	0,02	0,02	470	4	8	6
21064-060080	80	50	5,5	1,6	3,2	-	M3	M4	0,02	0,02	380	3	11	7
21064-060105	105	50	5,5	1,6	3,2	-	M3	M4	0,02	0,02	530	10	14	15
21064-060155	155	50	5,5	1,6	3,2	-	M3	M4	0,02	0,02	690	23	23	34
21064-075080	80	-	-	2,1	4,1	M5	M4	-	0,02	0,02	650	10	18	15
21064-075105	105	60	6	2,1	4,1	M5	M4	M5	0,02	0,02	720	18	26	27
21064-075130	130	60	6	2,1	4,1	M5	M4	M5	0,02	0,02	850	29	33	42
21064-100110	110	-	-	2,1	4,1	M6	M6	M6	0,02	0,02	1740	43	59	63
21064-100160	160	86	8	2,1	4,1	M6	M6	M6	0,02	0,02	1190	37	79	68
21064-100210	210	86	8	2,1	4,1	M6	M6	M6	0,03	0,03	1450	60	99	105
21064-100260	260	86	8	2,1	4,1	M6	M6	M6	0,03	0,03	1730	89	119	151