

## Item description/product images



## Description

**Material:**

Steel parts stainless steel 1.4305.  
Ball knob black plastic.

**Version:**

Stainless steel parts bright.  
Ball knob polished.

**Note:**

Tension levers can be used for simple clamping or control operations.  
Where applicable, there must be enough space available so that the grip can be rotated 360°.

**On request:**

Other internal threads, reamed holes and special versions.  
Dimension "A" available in other lengths at extra charge.

## Overview of items

| Order No.   | Thread type     | Form | Size | X   | T  | D  | D1 | D2 | H  | H1   | H2   | A     | A2 |
|-------------|-----------------|------|------|-----|----|----|----|----|----|------|------|-------|----|
| 06341-2082  | internal thread | 0°   | 1    | M8  | 18 | 24 | 10 | 25 | 40 | -    | 32,5 | 88,1  | -  |
| 06341-2102  | internal thread | 0°   | 1    | M10 | 18 | 24 | 10 | 25 | 40 | -    | 32,5 | 88,1  | -  |
| 06341-21012 | internal thread | 0°   | 2    | M10 | 20 | 28 | 12 | 32 | 46 | -    | 36,5 | 104   | -  |
| 06341-2122  | internal thread | 0°   | 2    | M12 | 20 | 28 | 12 | 32 | 46 | -    | 36,5 | 104   | -  |
| 06341-2162  | internal thread | 0°   | 3    | M16 | 23 | 33 | 13 | 32 | 52 | -    | 41   | 126,5 | -  |
| 06341-2202  | internal thread | 0°   | 4    | M20 | 26 | 41 | 13 | 32 | 61 | -    | 49   | 128,5 | -  |
| 06341-208   | internal thread | 20°  | 1    | M8  | 18 | 24 | 10 | 25 | 40 | 52,5 | 32,5 | 84,5  | 15 |
| 06341-210   | internal thread | 20°  | 1    | M10 | 18 | 24 | 10 | 25 | 40 | 52,5 | 32,5 | 84,5  | 15 |
| 06341-2101  | internal thread | 20°  | 2    | M10 | 20 | 28 | 12 | 32 | 46 | 61   | 36,5 | 100   | 15 |
| 06341-212   | internal thread | 20°  | 2    | M12 | 20 | 28 | 12 | 32 | 46 | 61   | 36,5 | 100   | 15 |
| 06341-216   | internal thread | 20°  | 3    | M16 | 23 | 33 | 13 | 32 | 52 | 72   | 41   | 121   | 15 |
| 06341-220   | internal thread | 20°  | 4    | M20 | 26 | 41 | 13 | 32 | 61 | 80   | 49   | 123   | 15 |
| 06341-1102  | reamed hole     | 0°   | 1    | 10  | 22 | 24 | 10 | 25 | 40 | -    | 32,5 | 88,1  | -  |
| 06341-1122  | reamed hole     | 0°   | 2    | 12  | 25 | 28 | 12 | 32 | 46 | -    | 36,5 | 104   | -  |
| 06341-1142  | reamed hole     | 0°   | 2    | 14  | 25 | 28 | 12 | 32 | 46 | -    | 36,5 | 104   | -  |
| 06341-1162  | reamed hole     | 0°   | 3    | 16  | 28 | 33 | 13 | 32 | 52 | -    | 41   | 126,5 | -  |
| 06341-1202  | reamed hole     | 0°   | 4    | 20  | 32 | 41 | 13 | 32 | 61 | -    | 49   | 128,5 | -  |
| 06341-110   | reamed hole     | 20°  | 1    | 10  | 22 | 24 | 10 | 25 | 40 | 52,5 | 32,5 | 84,5  | 15 |
| 06341-112   | reamed hole     | 20°  | 2    | 12  | 25 | 28 | 12 | 32 | 46 | 61   | 36,5 | 100   | 15 |
| 06341-114   | reamed hole     | 20°  | 2    | 14  | 25 | 28 | 12 | 32 | 46 | 61   | 36,5 | 100   | 15 |
| 06341-116   | reamed hole     | 20°  | 3    | 16  | 28 | 33 | 13 | 32 | 52 | 72   | 41   | 121   | 15 |
| 06341-120   | reamed hole     | 20°  | 4    | 20  | 32 | 41 | 13 | 32 | 61 | 80   | 49   | 123   | 15 |